



UFSC371GCP

Display Freezer

Product Features

- Illuminated canopy
- Heated glass to help prevent condensation
- LED interior light with switch
- Fixed freezing shelves
- Defrost water drain
- Digital temperature display
- Adjustable feet
- Lock

Display freezer with canopy and a heated glass door

Great product presentation at a competitive price – that is what you get with this display freezer. It has a heated glass door to prevent condensation and internal LED lighting to highlight your frozen goods. The illuminated canopy will attract the attention of customers and the cabinet is great for branding. The cooling system is static with 6 fixed freezing shelves with built-in evaporator coils to ensure an even temperature throughout the cabinet. The upright freezer comes with a defrost water drain for easy maintenance.

Measures and Content

Total Display Area	m ²	0.74
Temperature Range	°C	-24 to -14
Climate Class		4
Net Volume	l	270
Gross Volume	l	300
Gross / Net Volume	l	300 / 270
Gross / Net Weight	kg	100 / 95

Design and Material

No. of Doors		1
Door No & Type		1 heated hinged glass door
Max load on Shelves	kg/m ²	110
No. of Shelves	pcs	6
Shelf Color		Chrome
Shelf Dimensions		470 x 413 mm
Shelves No & Type		6 fixed freezing shelves
Tempered glass		Yes
Canopy Light		LED Cold White
Canopy Type		D-Shape
Feet / Legs		2 adjustable feet
Castors		2 rollers
Interior Light		LED
Lock		Yes
Exterior Finish		White
Interior Finish		White

Cooling and Functions

Type of Controller		Mechanical
Type of Cooling		Static
Type of Defrost		Manual
Refrigerant		R290
Refrigerant Charge	g	85
Thermometer		Yes

Power and Consumption

Energy Class		C
Max Ambient		+30°C, 55% RH
Annual Energy Cons.	kWh/year	3035
Energy Consumption	kWh/24h	8.32
EEl	%	34.7
Power Supply		13 Amp
Input Power	W	570
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	40

Dimensions

External Dimension (WxDxH)	mm	595 x 640 x 1980
Internal Dimension (WxDxH)	mm	470 x 440 x 1545
Packed Dimension (WxDxH)	mm	680 x 710 x 2050
40ft Container Load	pcs	54



Strong handle



Lock