



PC2500B

Supermarket Multideck Cooler

Product Features

- Frameless glass doors for great product visibility
- Low energy consumption
- Black interior and exterior
- Adjustable shelves with tilting function
- LED light under each shelf
- Ventilated cooling for fast pull-down and even temperature
- Digital controller and temperature display
- Glass end walls as standard
- 33 mm ticket strips with shelf risers included
- Castors and locking feet

Black multideck cooler with frameless glass doors

The PC multideck cooler is all about product visibility and comes with frameless glass doors as well as glass end walls. To further highlight the products, the cooler is equipped with horizontal LED lighting at the top of the cabinet and below each shelf. The 450 mm deep shelves are adjustable and have a tilting function for better product presentation. Front risers are included.

The PC is a spacious cooler with a low energy consumption, and you get a good quality for a competitive price. It is temperature class 3M1, which means it is suitable for display of packed fresh meat, dairy products, fresh fruit and vegetables and is ideal for supermarkets, convenience stores, delis or sandwich shops.

Measures and Content

Gross / Net Weight	kg	500 / 440
Net Volume	l	1529
Gross Volume	l	2585
Gross / Net Volume	l	2585 / 1529
Total Display Area	m²	5.13
Temperature Range	°C	-1 to +5
Climate Class		3

Design and Material

Exterior Finish		Black RAL9005
Interior Finish		Black RAL9005
No. of Doors		4
Door No & Type		4 hinged glass doors
Door Reversible		No
No. of Shelves	pcs	5
Shelves No & Type		5 adjustable
Shelf Color		Black
Max load on Shelves	kg/m²	160
Feet / Legs		6 adjustable feet
Castors		6 castors
Tempered glass		Yes
Interior Light		LED

Cooling and Functions

Type of Controller		Electronic
Type of Defrost		Automatic
Refrigerant		R290
Refrigerant Charge	g	2 x 149
Thermometer		Yes

Power and Consumption

Energy Class		B
Energy Consumption	kWh/24h	10.2
Annual Energy Cons.	kWh/year	3723
EEl	%	14.5
Input Power	W	1060
Voltage / Frequency	V/Hz	220-240/50
Noise Level	dB(A)	65

Dimensions

External Dimension (WxDxH)	mm	2560 x 740 x 2050
Internal Dimension (WxDxH)	mm	2500 x 450 x 1540
Packed Dimension (WxDxH)	mm	2610 x 762 x 2256
40ft Container Load	pcs	12



Display with a button for each feature



LED light under each shelf